



4600 PLUS LIFT & SLIDE

TBB

ENERGY EFFICIENCY

Thermal Transmission Coefficient
Uw ≥ 0.65 (W/m²K)

Please consult typology, dimensions and glazing

GLAZING

Maximum glazing: **65 mm**

CATEGORIES ACHIEVED AT TEST CENTRE

Protection against atmospheric agents

Air permeability (UNE-EN 12207):

Wind resistance (UNE-EN 12210):

Class 4

Class C5

SECTIONS	Frame 180 mm 3 rails 280 mm 4 rails 380 mm Sash 80 mm
MAXIMUM DIMENSIONS	Width (L) = 3300 mm Height (H) = 3300 mm
MAXIMUM WEIGHT	400 Kg

EXTRUSION ALLOY

6063 T-5

OPENING POSIBILITIES

Sliding

1 rail (1 sash + 1 fixed light), 2, 3 & 4 rails

Possibility of 90° opening without mullion

Please consult maximum dimensions according to types

FINISHES

Colour powder coating
(RAL, mottled, rough...)

According to Qualicoat Standard > 60 microns

Wood effect powder coating

According to Qualideco Standard

Anodized

According to Ewwa Euras

Standard Class 15

Optionally Class 20 y 25

Optionally bicoloured

